



4AC.008
Tape – Zetex®
NEWTEX

Overview

Since 1978, our partner Newtex has been offering products resistant to fire and extreme temperatures. Thanks to these properties, Newtex tapes are mainly used for thermal insulation and sealing of industrial furnaces.

Zetex® tapes can withstand temperatures up to 700 °C. They are available in several versions, coated or reinforced.

Technical Data

Properties		Unit	Value
Material			Glass
Composition		%	100 % Zetex®
Temperature	Operating	°C	540
	Peak		700

General Data

Material	Thermal resistivity	Mechanical strength	Chemical resistance
Zetex	★★★★☆	★★★★☆	★★★★☆ Except for phosphoric and hydrofluoric acid

Applications

- Thermal insulation
- Insulation of pipes and exhausts
- Expansion joints
- Sealing joint
- Insulation



Available tapes

Width (mm) \ Thickness (mm)	0.76	1.54	3.18	6.35
25.4		Zetex P-1050 1.0" Tape 1TEX001607	Zetex P-2150 1.0" Tape 1TEX001612	Zetex P-3900 1.0" Tape 1TEX001631
38.1			Zetex P-2150 1.5" Tape 1TEX001613	Zetex P-3900 1.5" Tape 1TEX001632
50.8	Zetex A-550 2.0" Tape 1TEX001606	Zetex P-1050 2.0" Tape 1TEX004857	Zetex P-2150 2.0" Tape 1TEX001614	Zetex P-3900 2.0" Tape 1TEX001633
76.2	Zetex A-550 3.0" Tape 1TEX004607	Zetex P-1050 3.0" Tape 1TEX001609	Zetex P-2150 3.0" Tape 1TEX001615	Zetex P-3900 3.0" Tape 1TEX001634
88.9			Zetex P-2150 3.5" Tape 1TEX001616	
101.6		Zetex P-1050 4.0" Tape 1TEX001610	Zetex P-2150 4.0" Tape 1TEX001617	
152.4		Zetex P-1050 6.0" Tape 1TEX001611	Zetex P-2150 6.0" Tape 1TEX001618	

The physical properties in this documentation are provided for informational purposes only and do not constitute a contractual commitment. Please contact our technical service if you require any additional information.